

TSC

The Smarter Choice.



TTP-246M PRO SERIES – Industrial Thermal Transfer Bar Code Printer **DURABLE HIGH QUALITY PERFORMANCE**



KEY FEATURES

- Heavy duty die-cast aluminum design
- 600-meter ribbon supply
- Large LCD display with 6-button menus
- USB 2.0, serial and parallel connectivity are standard
- Available in 203 and 300 dpi resolution versions
- Up to 203 mm (8") per sec. print speed
- 32-bit RISC processor
- TSPL-EZ™ firmware for plug-n-play ease
- Powerful basic programming tools
- Options include: Ethernet; USB host for use with keyboards and scanners; peel, present & rewind; cutter

APPLICATIONS

- Industrial-duty Printing
- Healthcare Patient Safety
- Compliance Labeling
- Work In Process
- Order Fulfillment
- Distribution
- Shipping/ Receiving
- Ticketing
- Electronics & Jewelry Labeling

TTP-246M PRO SERIES – Industrial Thermal Transfer Bar Code Printer

| PRINTER MODEL | TTP-246M Pro | TTP-344M Pro |
|---------------------------|--|----------------------------|
| Resolution | 8 dots/mm (203 DPI) | 12 dots/mm (300 DPI) |
| Printing method | Thermal Transfer & Direct Thermal | |
| Max. print speed | 203 mm (8")/second | 152 mm (6")/second |
| Max. print width | 108 mm (4.25") | 104 mm (4.09") |
| Max. print length | 2,286 mm (90") | 1,016 mm (40") |
| Enclosure | Die-cast aluminum base and frame/Metal cover with large clear media view window | |
| Physical dimension | 270 mm (W) x 308 mm (H) x 505 mm (D) 10.63" (W) x 12.13" (H) x 19.88" (D) | |
| Weight | 15 kg (33.07 lbs) | |
| Label roll capacity | 208.3 mm (8.2") OD | |
| Ribbon | 600 m long, max. OD 90 mm, 1" core (ink coated outside or inside) | |
| Ribbon width | 25.4 mm ~ 114.3 mm (1" ~ 4.5") | |
| Processor | 32-bit RISC CPU | |
| Memory | <ul style="list-style-type: none"> • 4 MB Flash memory • 8 MB SDRAM • SD Flash memory card reader for Flash memory expansion, up to 4 GB (dealer option) | |
| Interface | <ul style="list-style-type: none"> • RS-232 • Centronics • USB 2.0 • USB host, for scanner or PC keyboard (dealer option) • PS/2 keyboard (dealer option) • Internal Ethernet, 10/100 Mbps (dealer option) • GPIO (dealer option) • Bluetooth (user option) | |
| Power | Internal switching power supply • Input: AC 100-240V, 3A, 50-60Hz • Output: DC 24V, 3.3A, 80W | |
| LCD | Graphic type, 128 x 64 pixel, with back light | |
| Operation switch, button | 1 power switch, 6 operation buttons (Menu, Pause, Feed, Up, Down, Select) & 3 LEDs | |
| Sensors | <ul style="list-style-type: none"> • Gap transmissive sensor (position adjustable) • Black mark reflective sensor (position adjustable) • Head open sensor • Ribbon end sensor | |
| Real time clock | Standard | |
| Internal fonts | <ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font | |
| Bar code | <ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Logmars • 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztech | |
| Font and barcode rotation | 0, 90, 180, 270 degree | |
| Printer language | TSPL-EZ™ (Compatible to EPL, ZPL, ZPL II) | |
| Media type | Continuous, die-cut, fan-fold, tag, notched, black mark, perforated, care label (outside wound) | |
| Media width | 25.4 ~ 118 mm (1" ~ 4.6") | |
| Media thickness | 0.06 ~ 0.30 mm (2.36 ~ 11.81 mil) | |
| Media core diameter | 25.4 ~ 76.2 mm (1" ~ 3") | |
| Label length | 5 ~ 2,286 mm (0.20" ~ 90") | 5 ~ 1,016 mm (0.20" ~ 40") |
| Environment condition | Operation: 5 ~ 40°C, 20 ~ 85% non-condensing Storage: -40 ~ 60°C, 5 ~ 90% non-condensing | |
| Safety regulation | FCC Class A, CE Class A, C-Tick Class A, UL, CUL, TÜV/Safety, CCC, CB | |
| Environmental concern | Comply with RoHS, WEEE | |
| Accessories | <ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord | |
| Limited warranty | <ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first | |
| Factory options | N/A | |
| Dealer options | <ul style="list-style-type: none"> • Internal rewinding kit • Peel-off kit Multi-interface board: • Configuration 1: Internal Ethernet interface (10/100 Mbps) + PS/2 keyboard interface + SD Flash memory card reader • Configuration 2: USB host + Internal Ethernet interface (10/100 Mbps) + PS/2 keyboard interface + SD Flash memory card reader • Configuration 3: GPIO interface + USB host + Internal Ethernet interface (10/100 Mbps) + PS/2 keyboard interface + SD Flash memory card reader | |
| User options | <ul style="list-style-type: none"> • Bluetooth module (serial interface) • Regular cutter (full cut guillotine cutter) • Heavy duty cutter (rotary cutter) • Care label cutter (rotary cutter) • KP-200 Plus series keyboard • KU-007 Plus programmable smart keyboard | |



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd.
 Tel: +886 3 990 6677
 E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
 Tel: +1 657 258 0808
 E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office
 Tel: +52 (33) 3836 6682
 E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office
 Tel: +55 (11) 9597 8098
 E-mail: americas_sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
 Tel: +49 (0) 8106 37979 00
 E-mail: emea_sales@tscprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
 Tel: +7 495 249 9017
 E-mail: emea_sales@tscprinters.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
 Tel: +971 4 2533 069
 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
 Tel: +886 2 2218 6789
 E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
 Tel: +86 22 5981 6661
 E-mail: apac_sales@tscprinters.com